SOLAR PHOTOVOLTAIC MODULES PM80

Solar Photovoltaic Modules, type PM80 are manufactured using Mono Crystalline Silicon Solar Cells. These are high quality and high performance modules suitable for power generation. These modules have excellent durability to withstand extreme temperature and weather conditions of the high altitudes, deserts and coastal regions.

FEATURES

- Uses mono crystalline silicon Solar Cells.
- Suitable for DC 12V/24V systems or multiple there-of.
- Encapsulation of cells using UV stabilized polymer (EVA) and protective back cover using Tedler-Polyester-Tedlar.
- High transmission toughened glass superstrate and anodized aluminum frame for mounting.
- Long service Life.

APPLICATIONS

Lighting
 Telecommunication
 Television
 Refrigeration
 Railway Signalling
 Rural Electrification
 Remote Resort Power

5. Power Plants

SOLAR MODULE PM75SPECIFICATION

Electrical Parameters	PM 80
Maximum Power Rating Pmax. (Wp)*	80.0
Minimum Power Rating Pmin (Wp)*	75.0
Rated Current I _{MPP} (A)	4.6
Rated Voltage V _{MPP} (V)	17.5
Short Circuit Current Isc (A)	5.0
Open Circuit Voltage Voc (V)	21.5

Physical Parameters

No. of Cells (Nos) 36

Physical Dimension (mm) (L x W x T) $1200 \times 550 \times 35$

Weight (Kg) 7.5

Environmental Rating

NOCT **	(°C)	45 ±2
Maximum permitted module temperature	(°C)	-40 to + 85
Maximum permissible system voltage	(°C)	600
Relative Humidity at 85°C	(°C)	85

* Under Standard Test Conditions (STC):

Air Mass AM 1.5
Irradiance 1000 W/m²
Cell Temperature 25°C

** Nominal Operating Cell Temperature (NOCT) at:
Wind Speed 1m/s
Irradiance 800 W/m²
Ambient Temperature 20°C

^{**}Specification subject to change without prior notice due to continuous in-house improvements.



CENTRAL ELECTRONICS LIMITED

4, Industrial Area, Sahibabad - 201010 (U.P.) INDIA, Tel. 0091-120-2895151, 2895165

Fax: 0091-120-2895131, 2895165

Central Electronics Ltd E-mail : spv@celsolar.com
Website : www.celsolar.com